

The NT860 has been developed to provide high-speed stability, steering response and safety in all conditions while improving comfort and fuel economy throughout its long tread life.

RIM SIZE:	15 - 18 INCH
SERIES:	40 - 65
WIDTH:	185 - 245
SPEED RATING:	V - W

BEST FIT?

With a large size range to suit O.E. replacements as well as plus-size fitments for aftermarket wheels, the NT860 is perfect for the Holden Commodore, Cruze or Astra, Ford Falcon, Mondeo, Focus or Fiesta, Toyota Camry, Corolla or Yaris, Mazda 2, 3 or 6 and many other sedans, wagons or hatches.



RESPONSIVE TOURING CAR TYRE



ADVANCED TREAD PATTERN

An asymmetric pattern provides more void area to resist aquaplaning and higher stiffness for better traction, handling and steering response.



ROUND-EDGED GROOVES

Rounded tyre grooves are designed to provide excellent water drainage and improved safety in wet conditions.



F-SHAPED BLOCK PATTERN

An F-shaped block pattern offers a balance between siped biting edges and stiffness, optimising wet and dry performance.



QUIET WALL TECHNOLOGY

Serration within the tread grooves eliminates howling pipe resonance noises by disrupting airflow.



SILICA TREAD COMPOUND

A new silica compound offers lower rolling resistance and uncompromising grip in wet conditions.

NITTO**NT860****FUELED BY ENTHUSIASTS****PRODUCT DATA SHEET**

Version 1.0



Tyre Size	Load Index/ Speed Symbol	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
			Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
195/55R15	85V	7.9	595	201	274	219	289	6.0	5.5 - 6.5	551
185/60R15	88V	7.8	603	189	277	206	293	5.5	5.0 - 6.0	544
195/60R15	88V	7.9	615	201	282	219	299	6.0	5.5 - 6.5	533
185/65R15	88V	7.8	621	189	284	206	301	5.5	5.0 - 6.0	528
195/65R15	91V	7.9	635	201	290	219	308	6.0	5.5 - 6.5	516
205/65R15	94V	8.0	647	209	294	228	314	6.0	5.5 - 6.5	507
205/55R16	91V	8.0	632	214	291	233	307	6.5	6.0 - 7.0	519
215/55R16	93V	8.1	642	226	295	246	312	7.0	6.5 - 7.5	511
225/55R16	99W	7.7	654	233	300	254	317	7.0	6.5 - 7.5	501
205/60R16	96V	8.0	652	209	299	228	316	6.0	5.5 - 6.5	503
215/60R16	95V	8.1	664	221	304	241	322	6.5	6.0 - 7.0	494
225/60R16	98V	8.2	676	228	308	249	328	6.5	6.0 - 7.0	485
215/65R16	98V	8.1	686	221	312	241	333	6.5	6.0 - 7.0	478
215/45R17	91W	7.6	626	213	292	232	304	7.0	6.5 - 7.5	524
225/45R17	94W	7.7	634	225	295	245	308	7.5	7.0 - 8.0	517
235/45R17	93W	7.8	644	236	299	257	313	8.0	7.5 - 8.5	509
225/50R17	98W	8.2	658	233	304	254	319	7.0	6.5 - 7.5	498
215/55R17	94W	8.1	668	226	308	246	324	7.0	6.5 - 7.5	491
225/55R17	97W	8.2	680	233	313	254	330	7.0	6.5 - 7.5	482
225/60R17	99V	8.2	702	228	321	249	341	6.5	6.0 - 7.0	467
225/40R18	92W	7.7	637	230	299	251	309	8.0	7.5 - 8.5	515
245/40R18	97W	7.9	653	248	305	270	317	8.5	8.0 - 9.0	502
225/45R18	95W	7.7	659	225	307	245	320	7.5	7.0 - 8.0	498
235/45R18	98W	8.3	669	236	311	257	325	8.0	7.5 - 9.0	490
245/45R18	100W	7.9	677	243	314	265	329	8.0	7.5 - 8.5	484