

The NT420S is designed for owners of SUVs, utes and 4x4 vehicles that primarily drive on sealed roads and want to enjoy their time behind the wheel, delivering the sporty response and traction of an ultra-high-performance road tyre.

RIM SIZE: 16 - 22 INCH
SERIES: 35 - 60
WIDTH: 225 - 305
SPEED RATING: H - W

BEST FIT?

Available in many plus-sized wheel fitments for medium, large and 4WD vehicles, the NT420S is perfect for the Jeep Grand Cherokee, BMW X-series, VW Toureg or Amarok, Mercedes Benz M- or G-class, Audi Q-models and Mazda CX-models.



HIGH-PERFORMANCE SUV ROAD TYRE



DRY GRIP

Large outer tread blocks increase the amount of surface area in contact with the road, improving dry cornering and handling.



EVEN WEAR

An asymmetrical, non-directional tread pattern allows for cross-rotation, evening out the irregular wear that occurs across a vehicle's four corners.*



EFFECTIVE SIPING

Sipes are thin slits in a tread block that cut through water on the road surface to gain traction. Adding siping across the tread pattern provides additional biting edges to help maintain traction in wet weather.



WET TRACTION

A deep centre tread pattern effectively channels water for better wet-weather performance.



TYRE STABILITY

Slanted three-dimensional tread blocks reduce flex for improved handling and mid-corner stability.

*Consult your tyre retailer on the appropriate rotation pattern for your vehicle.

NITTO

NT420S

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET
Version 1.0



Tyre Size	Load Index/ Speed Symbol	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
			Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
275/60R16	109V	8.9	736	284	332	310	357	8.0	7.5 - 9.5	445
275/60R17	110V	8.9	761	275	344	300	369	8.0	7.5 - 9.5	431
225/65R17	106V	8.9	723	225	330	245	351	6.5	6.0 - 8.0	453
235/55R18	104V	8.5	717	239	330	261	348	7.5	6.5 - 8.5	457
255/55R18	109V	8.7	735	257	337	280	357	8.0	7.0 - 9.0	446
275/45R19	108Y	7.5	731	273	338	298	355	9.0	8.5 - 10.5	449
255/50R19	107V	8.7	739	265	341	289	359	8.0	7.0 - 9.0	444
275/45R20	110Y	7.0	756	273	351	298	367	9.0	8.5 - 10.5	434
265/50R20	111V	8.8	774	277	358	302	376	8.5	7.5 - 9.5	424
305/50R20	120H	10.8	814	316	373	344	395	9.5	8.5 - 11.0	403
265/35R22	102V	8.3	745	271	352	295	362	9.5	9.0 - 10.5	440
285/35R22	106W	7.8	757	285	357	310	367	10.0	9.5 - 11.0	433
305/40R22	114H	10.8	802	310	374	338	389	11.0	10.0 - 12.0	409