

The Trail Grappler® M/T blends the Mud Grappler's® off-road performance with the Terra Grappler's® on-road comfort to create an aggressive mud-terrain tyre that is quieter than most other muddies.

RIM SIZE: 15 - 20 INCH
SERIES: 55 - 75
WIDTH: 265 - 315
SPEED RATING: P - Q

BEST FIT?

The Trail Grappler® M/T suits the plus-sized demands of serious off-roaders, perfect for the Toyota HiLux, Landcruiser or Prado, Nissan Patrol or Navara, Mitsubishi Pajero or Triton, Ford Ranger or Everest, Isuzu D-Max or MU-X and Mazda BT-50.



MUD-TERRAIN LIGHT-TRUCK 4X4 TYRE



DUAL SIDEWALL DESIGNS

Each Grappler has two sidewall designs so you can choose how your tyres look. On the Trail Grappler® M/T, one side has stylised lettering with V-shaped buttresses and the other has traditional lettering with flat buttresses.



INTELLIGENT TREAD DESIGN

Using 3D computer simulation, Nitto's engineers systematically adjusted the size, shape and position of the tread blocks to create an aggressive, yet quiet off-road tyre with up to 36% less tyre noise!*



EXTREME SHOULDER GROOVES

Reinforced shoulder grooves provide extreme off-road performance by facilitating self cleaning and stone ejection without compromising tread block stiffness.



DEEP CENTRAL SIPING

Sipes are thin slits in a tread block that cut through water on the road surface to gain traction. Deep centre sipes decrease hydroplaning and increase traction in wet conditions.



MUD EVACUATION

A balanced void ratio efficiently removes mud and dirt from the tread to provide continuous off-road traction.

*Compared to Nitto Mud Grappler®

NITTO

Trail Grappler M/T

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET

Version 1.2



www.nitto tyre.com.au | 1800 648 867

NITTO TRAIL GRAPPLER® M/T [2/2]

Tyre Size	Load Index/Speed Symbol	Ply Rating	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
				Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
33X12.50R15	108Q	6	16.7	839	330	390	354	407	10.0	8.5 - 11.0	391
LT265/75R16	123/120P	10	15.0	810	267	361	291	393	7.5	7.0 - 8.0	405
LT285/75R16	126/123Q	10	15.2	839	298	390	308	407	8.0	7.5 - 9.0	391
LT315/75R16	127/124Q	10	15.9	884	326	411	349	429	8.5	8.0 - 11.0	371
LT265/70R17	121/118Q	10	15.0	812	280	378	295	394	8.0	7.0 - 8.5	404
LT295/70R17	121/118P	10	15.4	852	304	396	314	414	8.5	7.5 - 10.0	385
35X12.50R17	121Q	10	16.7	885	335	412	350	430	10.0	8.5 - 11.0	370
LT285/65R18	125/122Q	10	15.0	834	303	388	319	405	8.5	8.0 - 10.0	393
35x12.50R18	123Q	10	16.7	890	340	414	355	432	10.0	8.5 - 11.0	368
LT305/55R20	121/118Q	10	15.4	848	320	394	337	412	9.5	8.5 - 11.0	387
35X12.50R20	121Q	10	16.7	890	340	414	345	432	10.0	8.5 - 11.0	368
37X12.50R20	126Q	10	16.7	934	330	434	350	453	10.0	8.5 - 11.0	351