

The Trail Grappler® M/T blends the Mud Grappler's® off-road performance with the Terra Grappler's® on-road comfort to create an aggressive mud-terrain tyre that is quieter than most other muddies.

**RIM SIZE:** 15 - 20 INCH  
**SERIES:** 55 - 75  
**WIDTH:** 265 - 315  
**SPEED RATING:** P - Q

**BEST FIT?**

The Trail Grappler® M/T suits the plus-sized demands of serious off-roaders, perfect for the Toyota HiLux, Landcruiser or Prado, Nissan Patrol or Navara, Mitsubishi Pajero or Triton, Ford Ranger or Everest, Isuzu D-Max or MU-X and Mazda BT-50.

**MUD-TERRAIN LIGHT-TRUCK 4X4 TYRE****DUAL SIDEWALL DESIGNS**

Each Grappler has two sidewall designs so you can choose how your tyres look. On the Trail Grappler® M/T, one side has stylised lettering with V-shaped buttresses and the other has traditional lettering with flat buttresses.

**INTELLIGENT TREAD DESIGN**

Using 3D computer simulation, Nitto's engineers systematically adjusted the size, shape and position of the tread blocks to create an aggressive, yet quiet off-road tyre with up to 36% less tyre noise!\*

**EXTREME SHOULDER GROOVES**

Reinforced shoulder grooves provide extreme off-road performance by facilitating self cleaning and stone ejection without compromising tread block stiffness.

**DEEP CENTRAL SIPING**

Sipes are thin slits in a tread block that cut through water on the road surface to gain traction. Deep centre sipes decrease hydroplaning and increase traction in wet conditions.

**MUD EVACUATION**

A balanced void ratio efficiently removes mud and dirt from the tread to provide continuous off-road traction.

\*Compared to Nitto Mud Grappler®

# NITTO

# Trail Grappler M/T

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET

Version 1.3



www.nitto tyre.com.au | 1800 648 867

NITTO TRAIL GRAPPLER® M/T [2/2]

Tyre Size	Load Index/Speed Symbol	Ply Rating	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
				Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
33X12.50R15	108Q	6	16.7	839	330	390	354	407	10.0	8.5 - 11.0	391
LT265/75R16	123/120P	10	15.0	810	267	361	291	393	7.5	7.0 - 8.0	405
LT285/75R16	126/123Q	10	15.2	839	298	390	308	407	8.0	7.5 - 9.0	391
LT315/75R16	127/124Q	10	15.9	884	326	411	349	429	8.5	8.0 - 11.0	371
LT265/70R17	121/118Q	10	15.0	812	280	378	295	394	8.0	7.0 - 8.5	404
LT295/70R17	121/118P	10	15.4	852	304	396	314	414	8.5	7.5 - 10.0	385
35X12.50R17	121Q	10	16.7	885	335	412	350	430	10.0	8.5 - 11.0	370
37x12.50R17	124Q	8	16.7	934	318	412	347	453	10.0	8.5 - 11.0	351
LT285/65R18	125/122Q	10	15.0	834	303	388	319	405	8.5	8.0 - 10.0	393
35x12.50R18	123Q	10	16.7	890	340	414	355	432	10.0	8.5 - 11.0	368
LT305/55R20	121/118Q	10	15.4	848	320	394	337	412	9.5	8.5 - 11.0	387
35X12.50R20	121Q	10	16.7	890	340	414	345	432	10.0	8.5 - 11.0	368
37X12.50R20	126Q	10	16.7	934	330	434	350	453	10.0	8.5 - 11.0	351