

Available in both passenger and light-truck constructions, the Nitto Terra Grappler® blends off-road performance in wet and dry conditions with on-road comfort and quietness.

**RIM SIZE:** 16 - 20 INCH

**SERIES:** 45 - 75

**WIDTH:** 265 - 305

**SPEED RATING:** Q - T

### BEST FIT?

The Terra Grappler® suits daily drivers who like to head off the beaten track from time to time, perfect for the Toyota HiLux, Landcruiser or Prado, Nissan Patrol or Navara, Mitsubishi Pajero or Triton, Ford Ranger or Everest and Isuzu D-Max or MU-X.



## ALL-TERRAIN LIGHT-TRUCK 4X4 TYRE



### DUAL SIDEWALL DESIGNS

Each Grappler has two sidewall designs so you can choose how your tyres look. On the Terra Grappler®, one side has solid-outlined lettering and the other has striped lettering.



### MULTI-PURPOSE TREAD

Tread pattern void ratio has been balanced for off-road traction and on-road handling. Reinforced coupling joints between the outermost and central tread blocks minimise excessive tread flex, maximising traction and steering response while encouraging even wear.



### HIGH-DENSITY SIPING

Siping helps resist hydroplaning by cutting through pockets of water on road surfaces. Deep sipes and lateral voids effectively channel water away to maximise wet traction.



### ALL-TERRAIN VERSATILITY

Angled lateral voids channel water away in wet conditions and provide forward stability in dry conditions.



### OFF-ROAD PERFORMANCE

Staggered shoulder lugs provide additional biting edges in off-road conditions, especially in deep sand and loose dirt.

# NITTO

# TERRA GRAPPLER

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET

Version 1.2



Tyre Size	Load Index/ Speed Symbol	Ply Rating	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
				Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
265/70R16	112S	N/A	10.4	779	268	349	292	378	8.0	7.0-9.0	421
LT305/70R16	124/121Q	10	13.1	830	315	368	343	403	9.0	8.0-9.5	395
LT265/75R16	123/120Q	10	12.4	803	271	358	295	390	7.5	7.0-8.0	408
LT285/75R16	122/119Q	8	13.1	830	288	368	314	403	8.0	7.5-9.0	395
LT265/70R17	121/118R	10	12.4	803	278	361	303	390	8.0	7.0-8.5	408
275/45R20	110T	N/A	11.1	759	271	352	296	369	9.0	8.5-10.5	432
265/50R20	111S	N/A	10.6	775	273	358	297	376	8.5	7.5-9.5	423
285/50R20	116S	N/A	10.8	794	297	366	324	385	9.0	8.0-10.0	413
LT275/65R20	126/123R	10	12.4	866	279	394	304	420	8.0	7.5-9.5	379