

The NT860 has been developed to provide high-speed stability, steering response and safety in all conditions while improving comfort and fuel economy throughout its long tread life.

RIM SIZE: 15 - 18 INCH
SERIES: 40 - 65
WIDTH: 185 - 245
SPEED RATING: V - W

BEST FIT?

With a large size range to suit O.E. replacements as well as plus-size fitments for aftermarket wheels, the NT860 is perfect for the Holden Commodore, Cruze or Astra, Ford Falcon, Mondeo, Focus or Fiesta, Toyota Camry, Corolla or Yaris, Mazda 2, 3 or 6 and many other sedans, wagons or hatches.



RESPONSIVE TOURING CAR TYRE



ADVANCED TREAD PATTERN

An asymmetric pattern provides more void area to resist aquaplaning and higher stiffness for better traction, handling and steering response.



ROUND-EDGED GROOVES

Rounded tyre grooves are designed to provide excellent water drainage and improved safety in wet conditions.



F-SHAPED BLOCK PATTERN

An F-shaped block pattern offers a balance between siped biting edges and stiffness, optimising wet and dry performance.



QUIET WALL TECHNOLOGY

Serration within the tread grooves eliminates howling pipe resonance noises by disrupting airflow.



SILICA TREAD COMPOUND

A new silica compound offers lower rolling resistance and uncompromising grip in wet conditions.

NITTO

NT860

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET

Version 1.1



Tyre Size	Load Index/ Speed Symbol	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
			Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
195/55R15	85V	7.9	595	201	274	219	289	6.0	5.5 - 6.5	551
185/60R15	88V	7.8	603	189	277	206	293	5.5	5.0 - 6.0	544
195/60R15	88V	7.9	615	201	282	219	299	6.0	5.5 - 6.5	533
185/65R15	88V	7.8	621	189	284	206	301	5.5	5.0 - 6.0	528
195/65R15	91V	7.9	635	201	290	219	308	6.0	5.5 - 6.5	516
215/55R16	93V	8.1	642	226	295	246	312	7.0	6.5 - 7.5	511
215/45R17	91W	7.6	626	213	292	232	304	7.0	6.5 - 7.5	524
225/45R17	94W	7.7	634	225	295	245	308	7.5	7.0 - 8.0	517
225/50R17	98W	8.2	658	233	304	254	319	7.0	6.5 - 7.5	498
225/55R17	97W	8.2	680	233	313	254	330	7.0	6.5 - 7.5	482
225/60R17	99V	8.2	702	228	321	249	341	6.5	6.0 - 7.0	467
225/40R18	92W	7.7	637	230	299	251	309	8.0	7.5 - 8.5	515
245/45R18	100W	7.9	677	243	314	265	329	8.0	7.5 - 8.5	484