

The Dura Grappler® has been developed to offer good ride comfort, quiet performance and long wear life to meet the demands of 4x4 utes along with conventional 4WDs and SUVs.

RIM SIZE:	16 - 18 INCH
SERIES:	60 - 75
WIDTH:	245 - 275
SPEED RATING:	H - T

BEST FIT?

The Dura Grappler® suits heavy vehicles that spend the majority of their time on sealed roads with the strength to hit the dirt when duty calls, perfect for the Toyota HiLux, Landcruiser or Prado, Nissan Patrol or Navara, Mitsubishi Pajero or Triton, Ford Ranger or Everest and Isuzu D-Max or MU-X.



HIGHWAY-TERRAIN LIGHT-TRUCK 4X4 TYRE



DUAL SIDEWALL DESIGNS

Each Grappler has two sidewall designs so you can choose how your tyres look. On the Dura Grappler®, one side has a metal fin design and the other has a traditional design.



MULTI-RIB PATTERN

A multi-rib pattern helps improve tread life by linking the tread blocks to reduce tread flex, with the added benefit of reduced road noise.



ADVANCED SIPING

Siping helps resist hydroplaning by cutting through pockets of water on road surfaces. The Dura Grappler® is equipped with waved sipes to increase traction in wet conditions while maintaining tread block rigidity.



WET PERFORMANCE

Circumferential grooves evacuate water from the tread pattern to maintain traction in wet and slushy conditions.



SPECIFIC PATTERNS

The Dura Grappler® is offered in two separate tread patterns across light-truck and passenger constructions. The light-truck Dura Grappler® maximises strength with a durable 4-rib design while the 5-rib design of the passenger version minimises tyre noise.

NITTO

DURA GRAPPLER

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET

Version 1.3



Tyre Size	Load Index/ Speed Symbol	Ply Rating	Tread Depth (mm)	Inflated Dimensions		Loaded Dimensions			Measuring Rim Width (in)	Approved Rim Widths (in)	Revs /km
				Overall Dia. (mm)	Overall Width (mm)	Static Radius (mm)	Static Width (mm)	Dynamic Radius (mm)			
265/70R16	112H	N/A	10.4	779	273	348	298	378	8.0	7.0-9.0	421
275/65R17	115T	N/A	10.3	792	280	356	305	384	8.0	7.5-9.5	414
LT245/70R17	119/116R	10	12.5	777	246	351	268	377	7.0	6.5-8.0	422
LT265/70R17	121/118Q	10	13.3	807	261	362	284	392	8.0	7.0-9.0	406